



EN 60598-1	230V / 50Hz	IP 43	IK 07		650°C		RoHS	70W / 80W / 125W
------------	-------------	-------	-------	--	-------	--	------	------------------



Domeniul de utilizare: Iluminatul
ornamental de exterior

Descriere:

Fianșa de fixare: Din aliaj de aluminiu
turnat sub presiune

Capac superior: Din tablă de oțel vopsit
negru, gri, alb, galben

Dispensor: Din PMMA, rezistent la șocuri

Stâlp de fixare: max. Φ 52mm

Sursa: Mercur (HME), sodiu (HSE)

Dulie: E27

Standard: SR EN 60598-1

Application: Outdoor decorative lighting

Description:

Fixing flange: Diecast aluminum alloy

Top: Black, grey, white, yellow painted
steel sheet


Diffuser: PMMA, shock resistant

Fixing pole: Max. Φ 52mm

Source: Mercury (HME), sodium (HSE)

Socket: E 27

Standard: SR EN 60598-1



pg.321

	Tip/Type	Cod produs/ Product code	Dimensiuni/Dimensions [mm]		Factor de putere / Power factor	Masa/ Weight [kg]	Lampa/ Lamp
			φ	L			
PVC	1x80W negru / black	33421610	415	503	min. 0.92	6.45	HME
	1x125W negru / black	33431616	415	503	min. 0.92	6.50	
	1x80W alb / white	33421611	415	503	min. 0.92	6.45	
	1x80W gri / grey	33421612	415	503	min. 0.92	6.45	
	1x125W alb / white	33421619	415	503	min. 0.92	6.50	
PVSC	1x125W galben / yellow	33421625	415	503	min. 0.92	6.50	HSE
	1x70W negru / black	34421610	415	503	min. 0.92	6.70	
	1x70W galben / yellow	34421611	415	503	min. 0.92	6.70	
	1x125W gri / grey	34421612	415	503	min. 0.92	6.50	HME

