

PAR56 and PAR64

PAR56 300W 230V MFL

These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for longrange light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.

Product data

• General Characteristics

ANSI Code LIF Code Cap-Base GX16d Cap-Base Information Bulb

Operating Position any

Main Application Flood and Ambient Lighting

Average Lifetime 2000 hr Life to 50% failures 2000 (min) hr

• Light Technical Characteristics

Beam Description Medium Flood Beam Angle 20 D

Beam Angle Tech-20 D

30000 (max) cd Luminous Intensity

3000 K Color Temperature

• Electrical Characteristics

Lamp Wattage 300 W 230 V Voltage

Dimensional drawing

• Environmental Characteristics

Energy Efficiency Label (EEL)

Product Dimensions

Overall Length C 127 (max) mm Diameter D 178 (max) mm

• Product Data

Order code 924783644204 924783644204 Full product code PAR56 300W 230V MFL Full product name PAR56 300W 230V MFL Order product name

Pieces per pack Packing configuration Packs per outerbox

8711500441881 Bar code on pack -

EAN1

Bar code on 8711500441898 outerbox - EAN3

Logistic code(s) -


924783644204

12NC

542.000 kg Net weight per piece



Dimensional drawing



PAR56 300W 230V MFL

Product	C (Max)	D (Max)
PAR56 300W 230V MFL	127	178



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.