

PAR56 and PAR64

PAR64 1000W 230V VNSP

These self-contained spotlights are ideal for intensifying the visual experience in all kinds of clubs, that is because their accurate beam control picks out even the smallest of details even over long distances. This beam control makes the PAR 56 and PAR 64 excellent for longrange light projections. In addition, the universal burning feature provides complete flexibility of luminaires angle and position, while the front glass of the PAR56 provides thermal and physical protection. The result? Complete creative freedom to achieve the desired effect. Immediate re-strike also ensures instant resumption of entertainment after any power interruption.

Product data

• General Characteristics

ANSI Code EXC LIF Code CP60 Cap-Base GX16d

Cap-Base Information

Bulb PAR64 [PAR 64inch/180mm]

Operating Position

Main Application Flood and Ambient Lighting

Gas Filling GAS 300 hr Average Lifetime Life to 50% failures 300 (min) hr

• Light Technical Characteristics

Beam Description Very Narrow Spot

Beam Angle 11 D Beam Angle Tech-

nical

Luminous Intensity 400000 (max) cd

Color Temperature 3200 K

• Electrical Characteristics

Lamp Wattage 1000 W

Dimensional drawing

230 V Voltage Dimmable Yes

Product Dimensions

Overall Length C 150 (max) mm 204 (max) mm Diameter D

• Product Data

924783244204 Order code 924783244204 Full product code

PAR64 1000W 230V VNSP Full product name Order product name PAR64 1000W 230V VNSP

8711500440860

924783244204

Pieces per pack Packing configuration Packs per outerbox

8711500440853 Bar code on pack -

EAN1

Bar code on

outerbox - EAN3


Logistic code(s) -

12NC

Net weight per piece 760.000 gr



Dimensional drawing



PAR64 1000W 230V VNSP

Product	C (Max)	D (Max)
PAR64 1000W 230V VNSP	150	204



Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.