

Standard Ballasts

5–16 W, 230 V

For compact fluorescent lamps
Shape: 28x41 mm

Vacuum-impregnated with polyester resin


Push-in terminal for leads: 0.5–1 mm²

For the automatic luminaire wiring:

IDC terminals for leads H05V-U 0.5

tw 130

Protection class I



Lamp				Ballast									Capacitor	
Output	Type	Base	Current	Type	Ref. No.	V, Hz	a	b	c	Weight	Δt/Δt _{on}	EEL*	C _P	Current
W			mA				mm	mm	mm	kg	K		μF	mA
230 V, 50 Hz														
5	TC-S	G23	180	L 7/9/11.851	503875	230, 50	85	75	27	0.28	65/100	B2	2.0	50
				L 7/9/11.307	163694	230, 50	85	75	34	0.32	60/85	B2	2.0	50
2x5	TC-S	G23	180	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	70
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	70
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	70
7	TC-S	G23	175	L 7/9/11.851	503875	230, 50	85	75	27	0.28	65/100	B2	2.0	50
				L 7/9/11.307	163694	230, 50	85	75	34	0.32	60/85	B2	2.0	50
2x7	TC-S	G23	160	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	70
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	70
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	70
9	TC-S	G23	170	L 7/9/11.307	163694	230, 50	85	75	34	0.32	60/85	B1	2.0	60
				L 7/9/11.851	503875	230, 50	85	75	27	0.28	65/100	B2	2.0	60
2x9	TC-S	G23	140	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	70
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	80
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	80
10	TC-D	G24d-1	190	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	70
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	70
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	70
10	TC-DD	GR10q	180	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	70
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	70
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	70
11	TC-S	G23	155	L 7/9/11.307	163694	230, 50	85	75	34	0.32	60/85	B1	2.0	80
				L 7/9/11.851	503875	230, 50	85	75	27	0.28	65/100	B2	2.0	80
13	TC-D/TC-T	G24d-1/GX24d-1	175	LN 13.805	169647	230, 50	85	75	34	0.32	50/85	B1	2.0	80
				L 13.849	503868	230, 50	85	75	27	0.28	65/110	B2	2.0	80
				LN 13.313	163711	230, 50	85	75	34	0.32	55/80	B2	2.0	80
16	TC-DD	GR8/GR10q	195	LN 16.316	163730	230, 50	85	75	34	0.32	60/125	B1	2.0	100

* Energy efficiency: EEL=B2 and EEL=B1, valid until 2017