



MASTERC colour CDM-Tm Mini GU6.5

MASTERC colour CDM-Tm Mini GU6.5 20W/830 1CT

Miniature, single-ended ceramic metal halide lamp GU6.5 twist-lock lamp base, according to global IEC standard

Product data

• General Characteristics

Cap-Base	GU6.5 [GU6.5]
Bulb	T-4
Bulb Finish	Clear
Operating Position	any [Any or Universal (U)]
Life to 5% failures	9000 hr
Life to 10% failures	10000 hr
Life to 20% failures	12000 hr
Life to 50% failures	15000 hr

Lumen Maintenance 12000h	77 %
Lumen Maintenance 15000h	75 %
Design Mean Lumens EL	1400 Lm
Chromaticity Coordinate X	0.436 -
Chromaticity Coordinate Y	0.396 -

• Light Technical Characteristics

Color Code	830 [CCT of 3000K]
Color Rendering Index	81 (min), 84 (nom) Ra8
Color Designation (text)	Warm White
Color Temperature	3000 K
Color Temperature Technical	2950 K
Luminous Flux Lamp EL	1800 Lm
Luminous Efficacy Lamp EL	90 Lm/W
Lumen Maintenance 1000h	91 %
Lumen Maintenance 2000h	87 %
Lumen Maintenance 4000h	84 %
Lumen Maintenance 5000h	83 %
Lumen Maintenance 8000h	80 %
Lumen Maintenance 10000h	78 %

• Electrical Characteristics

System Power EL	23.5 W
Lamp Wattage	20 W
Lamp Wattage EL 25°C, Rated	20.0 W
Lamp Wattage EL 25°C, Nominal	20.0 W
Lamp Voltage	94 V
Lamp Current EL	0.215 A
Ignition Time	30 (max) s
Run-up time 90%	3 (max) min
Re-ignition Time [min]	15 (max) min
Dimmable	No

• Environmental Characteristics

Energy Efficiency Label (EEL)	A+
Mercury (Hg) Content	3.5 mg
Energy consumption kWh/1000h	22 kWh

PHILIPS

MASTERColour CDM-Tm Mini GU6.5

• UV-related Characteristics

Damage Factor D/fc PET (NIOSH)	0.5 (max) - 8 (min) h500lx
-----------------------------------	-------------------------------

• Luminaire Design Requirements

Cap-Base Temperature	250 (max) C
Bulb Temperature	380 (max) C

• Product Dimensions

Overall Length C	56.7 (max) mm
Diameter D	13.3 (max) mm
Light Center Length L	29.7 (min), 30 (nom), 30.3 (max) mm
Arc Length O	3.5 mm
Light Center Length L [inch]	1.18 in
Overall Length C [inch]	2.25 (max) in

Diameter D [inch] 0.5 in

• Product Data


Order code	928183505130
Full product code	928183505130
Full product name	MASTERColour CDM-Tm Mini GU6.5 20W/830 1CT
Order product name	MASTERC CDM-Tm Mini GU6.5 20W/830 1CT/12
Pieces per pack	1
Packing configuration	12
Packs per outerbox	12
Bar code on pack - EAN1	8727900890839
Bar code on outerbox - EAN3	8727900890846
Logistic code(s) - 12NC	928183505130
ILCOS code	MT/UB-20/830-H-GU6.5-13.3/52
Net weight per piece	0.007 kg

Warnings and Safety

- Use only in totally enclosed luminaire, even during testing (IEC61167, IEC 62035, IEC60598)
- The luminaire must be able to contain hot lamp parts if the lamp ruptures

- Use only with electronic control gear
- Control gear must include end-of-life protection (IEC61167, IEC 62035)


Dimensional drawing




MASTERColour CDM-Tm Mini GU6.5 20W/830 1CT

Product	C (Max)	D (Max)	L (Min)	L (Norm)	L (Max)	O (Min)	O (Norm)	O (Max)
CDM-Tm 20W/830 GU6.5	56.7	13.3	29.7	30	30.3	-	3.5	-

Dimensional drawing



Photometric data



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, March 29
data subject to change