



MASTER TL-D Xtra

MASTER TL-D Xtra 36W/840 1SL

This TL-D Xtra lamp offers a longer lifetime and guarantees fewer early failures. This results in low maintenance costs and saves on expensive spot replacement. It is therefore suitable for places where lamp replacement is expensive due to high ceilings or disturbance of operations. This lamp can be operated on existing gear or dedicated HF Xtreme gear.

Product data

• General Characteristics

Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Cap-Base Information	Green Plate
Bulb	T8 [26 mm]
Life to 10% failures EM	30000 hr
Life to 10% fail	47000 hr
Preheat EL,3h	
Life to 10% fail	19000 hr
Nonpreh EL,3h	
Life to 50% failures EM	36000 hr
Life to 50% fail	55000 hr
Preheat EL,3h	
Life to 50% fail	22000 hr
Nonpreh EL,3h	
LSF EM 2000h Rated, 3h cycle	100 %
LSF EM 4000h Rated, 3h cycle	99 %
LSF EM 6000h Rated, 3h cycle	99 %
LSF EM 8000h Rated, 3h cycle	99 %
LSF EM 12000h Rated,3h cycle	99 %
LSF EM 16000h Rated,3h cycle	99 %
LSF EM 20000h Rated,3h cycle	99 %

• Light Technical Characteristics

Color Code	840 [CCT of 4000K]
Color Rendering Index	85 Ra8

Color Designation (text)	Cool White
Color Temperature	4000 K
Luminous Flux EM 25°C, Rated	3350 Lm
Luminous Flux EM 25°C, Nominal	3350 Lm
Lum Efficacy Rated EM 25°C	93 Lm/W
Luminance Average EM	1.25 cd/cm2
LLMF EM 2000h Rated	96 %
LLMF EM 4000h Rated	95 %
LLMF EM 6000h Rated	94 %
LLMF EM 8000h Rated	93 %
LLMF EM 12000h Rated	92 %
LLMF EM 16000h Rated	91 %
LLMF EM 20000h Rated	90 %
Design Temperature	25 C
Chromaticity Coordinate X	381 -
Chromaticity Coordinate Y	377 -

• Electrical Characteristics

Lamp Wattage	36 W
Lamp Wattage EM 25°C, Nominal	37 W

MASTER TL-D Xtra

Lamp Wattage EM 25°C, Rated	37.0 W
Lamp Voltage EM 25°C	104 V
Lamp Current EM 25°C	0.435 A
Dimmable	Yes

• Environmental Characteristics

Energy Efficiency Label (EEL)	A
Mercury (Hg) Content	3.0 mg
Energy consumption kWh/1000h	43 kWh

• Product Dimensions

Base Face to Base Face A	1199.4 (max) mm
--------------------------	-----------------

Insertion Length B	1204.1 (min), 1206.5 (max) mm
Overall Length C	1213.6 (max) mm
Diameter D	28 (max) mm

• Product Data

Order code	927982484014
Full product code	927982484014
Full product name	MASTER TL-D Xtra 36W/840 1SL
Order product name	MASTER TL-D Xtra 36W/840 1SL/25
Pieces per pack	1
Packing configuration	25
Packs per outerbox	25
Bar code on pack - EAN1	8711500558763
Bar code on outerbox - EAN3	8711500558794
Logistic code(s) - 12NC	927982484014
ILCOS code	FD-36/40/1B-E-G13
Net weight per piece	138.400 gr

Warnings and Safety


- To achieve published lifetimes for 100% operation, do not dim below 30%

- When used on electromagnetic gear, it is strongly recommended to apply only Philips S10 or S10E starters (for 18W types S2 or S2E) to achieve the published lifetimes, and to install new starters when relamping.

Dimensional drawing



MASTER TL-D Xtra 36W/840 1SL

Product	A (Max)	B (Min)	B (Max)	C (Max)	D (Max)
TL-D Xtra 36W/840	1199.4	1204.1	1206.5	1213.6	28



G13

Photometric data



© 2014 Koninklijke Philips N.V. (Royal Philips)
All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting

2014, March 31
data subject to change